



Australian Government
Civil Aviation Safety Authority

Instrument number CASA EX128/21

I, ROBERT KENNETH WALKER, Executive Manager, Regulatory Oversight, a delegate of CASA, make this instrument under regulations 11.160 and 11.205 of the *Civil Aviation Safety Regulations 1998*.

[Signed Rob Walker]

Robert Walker
Executive Manager, Regulatory Oversight

14 November 2021

CASA EX128/21 — Standard Take-off and Landing Minima (AirBridgeCargo Airlines) Exemption 2021

1 Name

This instrument is *CASA EX128/21 — Standard Take-off and Landing Minima (AirBridgeCargo Airlines) Exemption 2021*.

2 Repeal of instrument CASA EX173/18

Instrument *CASA EX173/18 — Standard Take-off and Landing Minima (AirBridgeCargo Airlines) Exemption 2018* is repealed.

3 Definitions

Note In this instrument, certain terms and expressions have the same meaning as they have in the *Civil Aviation Act 1988* and the regulations. These include: *aerodrome, air traffic control, low-visibility approach, low-visibility operation, low-visibility take-off, pilot in command* and *runway visual range*.

In this instrument:

ATC means air traffic control.

CAT means category, and refers to the various categories of precision approach operations mentioned in this instrument.

DH means decision height.

LVO means low-visibility operation.

LVP means low-visibility procedures applied by ATC at an aerodrome for protecting aircraft operations during conditions of reduced visibility or low cloud.

M/M means the particular make and model of an aircraft.

RVR means runway visual range.

4 Application

This instrument applies in relation to AirBridgeCargo Airlines LLC of Russia, ARN 773583 (the *exempted operator*), if:

- (a) the exempted operator conducts a flight to or from an aerodrome in any of the following kinds of aircraft (the *aircraft*): B747-8F, B747-400F, B777F; and
- (b) ATC at the aerodrome has informed the pilot in command of the aircraft that LVP are in force.

5 Exemptions

- (1) The exempted operator is exempt from compliance with subregulations 257 (3) and (4) of CAR.
- (2) The pilot in command of the aircraft is exempt from compliance with subregulations 257 (3) and (4) of CAR in relation to the flight.

6 Conditions

- (1) It is a condition of the exemption in subsection 5 (1) that the exempted operator ensures compliance with the requirements mentioned in subsection (3).
- (2) It is a condition of the exemption in subsection 5 (2) that the pilot in command of the aircraft ensures compliance with the requirements mentioned in subsection (3).
- (3) The requirements are:
 - (a) the aircraft must comply with the meteorological minima for LVO and associated requirements set out in Schedule 1; and
 - (b) the requirements for LVO mentioned in Schedule 2.

7 Repeal of this instrument

This instrument is repealed at the end of 31 October 2024.

Note Approval to conduct a low-visibility operation under this instrument may cease at an earlier date in accordance with subregulation 202.416 (3) of CASR. See the *Civil Aviation Legislation Amendment (Flight Operations—Consequential Amendments and Transitional Provisions) Regulations 2021*.

Schedule 1 Operating minima for LVO

Low-visibility take-off minima

- 1 An aircraft of a kind mentioned in column 1 of Table 1 must not conduct a low-visibility take-off from the aerodrome if the reported RVR for the take-off is less than the meteorological minimum mentioned in column 2 of the Table.

Table 1: Low-visibility take-off minima

Aircraft M/M (column 1)	Meteorological minimum (column 2)
B747-8F, B747-400F	150 m
B777F	125 m

Low-visibility approach minima

- 2 An aircraft of a kind mentioned in column 1 of Table 2, when conducting a low-visibility approach operation mentioned in column 2 of the Table for the purpose of landing the aircraft:
 - (a) has the RVR meteorological minimum mentioned in column 3 of the Table for the low-visibility approach operation; and

- (b) must apply the DH mentioned in column 4 of the Table for the low-visibility approach operation.

Table 2: Approach minima and requirements

Aircraft M/M (column 1)	Low-visibility approach operation (column 2)	RVR minimum (column 3)	DH (column 4)
B747-8F, B747-400F, B777F	CAT II	300 m	100 ft DH
	CAT IIIA	175 m	50 ft DH
	CAT IIIB	75 m	No DH

Schedule 2 Requirements for LVO

Operating minima and procedures

- 1 The requirements for conducting LVO are the most restrictive of the requirements in the following:
 - (a) this instrument;
 - (b) the LVO authorisation issued to the exempted operator by the Federal Air Transport Agency of the Russian Federation, and the terms and conditions for LVO associated with that authorisation.

Approach ban

- 2 For landings, the following approach ban rules apply:
 - (a) when making an approach, the pilot in command of the aircraft must ensure that the aircraft does not continue beyond 1 000 ft above aerodrome elevation if a controlling zone RVR is reported by ATC as continually less than the specified minimum for the landing;
 - (b) if, after passing 1 000 ft above aerodrome elevation, a controlling zone RVR is reported by ATC as falling below the specified minimum, the pilot in command of the aircraft may continue the approach to the minimum.
-